| FINANCIAL BID FOR FURNISHING WORK PUNJAB GRAMIN BANK, BRANCH - MANN SINGH WALA, MUKTSAR |  |       |        |          |          |
|---|--|-------|--------|----------|----------|
| S. No.  | <b>Description of items</b>  | Qty   | Unit   | Rate     | Amount   |
|   |  |       |        | (In Rs.) | (In Rs.) |
| 1.  | CLERICAL COUNTER   | 41/2' | Rft.   |          |          |
|   | P & F Clerical Counter 4'-6" x 2'-6"X 2'-6" Ht. with 12" high, 12  |       |        |          |          |
|   | mm thick glass on front with required wooden/aluminums supports.   |       |        |          |          |
|   | Counter shall have wooden partition 4'-0"x4'-0" with both side 1   |       |        |          |          |
|   | mm thick laminate & teak wood molding & all around duly  |       |        | 3-1      |          |
|   | polished on one side of counter. Counter shall be made of 19 mm  |       |        |          |          |
|   | thick commercial board of Duro / Century/ kit ply. It shall be   |       |        |          |          |
|   | finished with 1 mm thick laminate of <b>CEDAR WHITE</b> color on all sides of counter. The rates also include drawer with Hettich ball |       |        |          |          |
|   | bearing slides, cabinet box etc. Counters are to be provided with  |       |        |          |          |
|   | computer keyboard tray of Ebco make code no KBT 45 and drawers   |       |        |          |          |
|   | and boxes also making position for electrical points conduits &  |       |        |          |          |
|   | switch boxes with plastic round shape 2" diameter openings etc also  |       |        |          |          |
|   | fitting of U.P.S shelf, foot rest of 3" x 1.5" in C.P. teak wood at  |       |        |          |          |
|   | the bottom. I.e. complete job in all respects with fitting and   |       |        |          |          |
|   | accessories like Godrej locks, handles, hinges etc. Lower portion 4"   |       |        |          |          |
|   | wide shall be in burgundy color laminate (Bank shade) on front and   |       |        |          |          |
|   | side. Edges of the counter shall have teak wood molding duly   |       |        |          |          |
|   | polished. Edges shall be covered with teak wood molding/margin   |       |        |          | AL VIEW  |
|   | duly burgundy color (Bank color) polished.   |       |        | 12.0     |          |
| 2.  | OFFICER TABLE WITH SIDE RACK   | 5'    | Rft.   |          |          |
|   | (5'-0"x 2'-6", Side Rack- 3'-3" x 1'-3")   |       |        |          |          |
|   | P & F Officer Table 5'-0" x 2'-6"X 2'-6" Ht. with 12" high, 12   |       |        |          |          |
|   | mm thick glass on front with required wooden/aluminums supports.   |       |        |          |          |
|   | works include side rack 3'-6" x 1'-6" x 2'-0". Table & side rack   |       |        |          |          |
|   | shall be made with 19 mm thick commercial board of Duro /  |       |        |          |          |
|   | Century/ kit ply. It shall be finished with 1 mm thick laminate of   |       |        |          |          |
|   | CEDAR WHITE color on all sides of counter. The rates also  |       |        |          |          |
|   | include drawer with Hettich ball bearing slides, cabinet box etc.  |       |        |          |          |
|   | Counters are to be provided with computer keyboard tray of Ebco  |       |        |          |          |
|   | make code no KBT 45 and drawers and boxes also making position for electrical points conduits & switch boxes with plastic round        |       |        |          |          |
|   | shape 2" diameter openings etc also fitting of U.P.S shelf, <b>foot rest</b>   |       |        |          |          |
|   | of 3" x 1.5" in C.P. teak wood at the bottom. I.e. complete job in   |       |        |          |          |
|   | all respects with fitting and accessories like Godrej locks, handles,  |       |        |          |          |
|   | hinges etc. Lower portion 4" wide shall be in burgundy color   |       |        |          |          |
|   | laminate (Bank shade) on front and side. Edges of the counter shall  |       |        |          |          |
|   | have teak wood molding duly polished. Edges shall be covered with  |       |        |          |          |
|   | teak wood molding/margin duly burgundy color (Bank color)  |       |        |          |          |
|   | polished.  |       |        |          |          |
| 3.  | CASHIER COUNTER (With Door Closer)   | 6'    | Rft.   |          |          |
|   | Providing and fixing of CASHIER counter 6'-0" x 2'-6" wide, 3'-9"  |       |        |          |          |
|   | high shall be made of 19 mm. thick commercial board of Duro/   |       |        |          |          |
|   | Century/kit ply and finished with 1mm. CEDAR WHITE color   |       |        |          |          |
|   | laminate on all vertical & exposed and visible surfaces of counter.  |       |        |          |          |
|   | Counters are to be provided with computer keyboard tray of Ebco  |       |        |          |          |
|   | make code no KBT 45 and drawers with hettich ball bearing slides   |       |        |          |          |
|   | for drawer slides with partition for keeping currency and boxes.   |       |        |          |          |
|   | Also marking position for electrical points conduits & switch boxes  |       |        |          |          |
|   | with plastic round shape 2" diameter openings etc also fitting of  |       |        |          |          |
|   | U.P.S. shelf at bottom, i.e. complete job in all respects with fittings and accessories like godrej locks, handles, hinges etc. Lower  |       |        |          |          |
|   | portion 4" wide shall be in burgundy color laminate (Bank shade)   |       |        |          |          |
|   | on front and side. Edges of the counter shall have teak wood   |       |        |          |          |
|   | molding duly polished.   |       | LL CLL |          |          |



| 4.                                    | MANAGER TABLE 6'-0" X 2'-6" with side rack & Back rack   | 1   | Nos.  |     |      |
|---------------------------------------|--|-----|-------|-----|------|
|                                       |  |     | 1103. |     | <br> |
|                                       | 1 " " " " Utall the made of 10 mm 41'1   | - 1 |       |     |      |
|                                       | John Cital Oddid/ Distion Board Ton and  |     |       |     |      |
|                                       | 1 - March Have Hill Thick William CED in   |     |       |     |      |
|                                       | The carried with Calbung lable all evnoced adopt about 1   |     |       |     |      |
|                                       |  |     |       |     |      |
|                                       | color laminate (Bank shada) or for the wide shall be in burgundy   |     |       |     |      |
|                                       | color laminate (Bank shade) on front and side. The rate also   |     |       |     |      |
|                                       |  |     |       |     |      |
|                                       |  |     |       |     |      |
|                                       |  |     |       |     |      |
|                                       |  |     |       |     |      |
|                                       | The complete loo in all respects   |     |       |     |      |
| 5.                                    | MANAGER TABLE - TOP GLASS  | +   |       |     |      |
|                                       | 6'-0" X 2'-6" x 8 MM with Grinding of Edges & Corners.   | 1   | Nos.  | 1   |      |
| 6.                                    | OFFICER TABLE - TOP GLASS  |     |       | a.s |      |
|                                       | 5'-0" X 2'-6" x 8 MM with Cai- 1'  | 1   | Nos.  |     |      |
| 7.                                    | 5'-0" X 2'-6" x 8 MM with Grinding of Edges & Corners.   |     |       |     |      |
|                                       | ABOMINION PARTITION  |     |       |     |      |
|                                       | CASHIER CABIN 7' HT.   | 120 | Cart  |     |      |
|                                       | Aluminum section shall be 4" x 1.75" x 2 mm ivory color powder   | 120 | Sqft. |     |      |
|                                       | Tartiful Slidii liave A mm thick gloca as C  |     |       |     |      |
|                                       | 1 PPOLITICITY J = 0 III SDAIL have x mm think 1 0 0  |     |       |     |      |
|                                       | portact could iddl on walls bront of the1:   |     |       |     |      |
|                                       | horizontal gap of 2" width at the front so that customer & cashier   |     |       |     |      |
|                                       | can listen to each other. Lower 3'-6" Ht. Portion shall have pre   |     |       |     |      |
|                                       | laminated board / Bison Board L. Portion shall have pre –  |     |       |     |      |
|                                       | laminated board / Bison Board Ivory color fixed in aluminum frame  |     |       |     |      |
|                                       |  |     |       |     |      |
|                                       |  |     |       |     |      |
|                                       | Title of Studdies Handles hinges door of the   |     |       |     |      |
|                                       | the cusine door etc complete ion in all respects   |     |       |     |      |
|                                       | MANAGER CABIN PARTITION 5' A" HT   |     |       |     |      |
|                                       | P&F Manager Cabin Partition of aluminum 52 on the com  | 80  | Sqft. |     |      |
|                                       | " = min tyory color powder coated pine I array Design as an array  |     |       |     |      |
|                                       | shall have pre -laminated board / Bison Board Ivory color fixed in   |     |       |     |      |
| - 1                                   | aluminum frame matching with the Ivory color lamination. Upper   |     |       |     |      |
|                                       | portion of the partition shall be  |     |       |     |      |
|                                       | of the partition shall have 6 mm thick along Th  |     |       |     |      |
| 3.                                    | a shaped ileopietie backer   |     |       |     |      |
|                                       | MAIN ENTERANCE DOOR & BACK DOOR  | 120 | Cast  |     |      |
|                                       | 1 & F of aluminum door 8' Ht high on man 1 ' The   | 120 | Sqft. |     |      |
|                                       | storion should be 4 x 1 /3 y / mm for from 0   |     | 1 1   |     |      |
|                                       | Total Control of the language 17 (17) Line in |     |       |     |      |
|                                       | The state of the s |     |       |     |      |
|                                       | aluminum frame of ivory color. Upper part shall have 6 mm thick  |     |       |     |      |
|                                       | glass. These aluminum frames included shall have 6 mm thick  |     |       |     |      |
|                                       | glass. These aluminum frames includes channels, beading & u  |     |       |     |      |
|                                       |  |     |       |     |      |
|                                       | Trems such as Goulet locks stonners handles de l   |     |       |     |      |
| 15.                                   | and seed, i.e. Complete lob in all respects  |     |       |     |      |
| 1                                     | EAL CE CEVE TO CONTRACT OF THE |     |       |     |      |
|                                       | FALSE CEILING (at 8'-6" high)  | 470 | C - C |     |      |
| 1<br>  1<br>  I                       | P & F in position false ceiling in Armstron (00 V 60)  | 470 | Sqft. |     |      |
|                                       | P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by A   | 470 | Sqft. |     |      |
| I I r                                 | PALSE CEILING (at 8'-6" high)  2 & F in position false ceiling in Armstrong 600 X 600 mm x 15/16  mm Dune Supreme RH 99 Prima file as specified by Armstrong Co.  with suspenders wherever required making pages.  | 470 | Sqft. |     |      |
| I I r                                 | PALSE CEILING (at 8'-6" high)  2 & F in position false ceiling in Armstrong 600 X 600 mm x 15/16  mm Dune Supreme RH 99 Prima file as specified by Armstrong Co.  with suspenders wherever required making pages.  | 470 | Sqft. |     |      |
| I I I I I I I I I I I I I I I I I I I | PALSE CEILING (at 8'-6" high)  2 & F in position false ceiling in Armstrong 600 X 600 mm x 15/16  mm Dune Supreme RH 99 Prima file as specified by Armstrong Co.  with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for different statements of the suprementation of the supremen | 470 | Sqft. |     |      |
| 1   1   1   r   v   A   f   f         | PALSE CEILING (at 8'-6" high)  2 & F in position false ceiling in Armstrong 600 X 600 mm x 15/16  mm Dune Supreme RH 99 Prima file as specified by Armstrong Co.  with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light littings, taping and finished to proper line & level include.  | 470 | Sqft. |     |      |
| I I I I I I I I I I I I I I I I I I I | PALSE CEILING (at 8'-6" high)  P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16  mm Dune Supreme RH 99 Prima file as specified by Armstrong Co.  with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light ittings, taping and finished to proper line & level including making croves and trap doors for A.C. Unit in 18 mm this land.   | 470 | Sqft. |     |      |
| I I I I I I I I I I I I I I I I I I I | P&F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making croves and trap doors for A.C. Unit in 18 mm thick M.R. Grade lywood with stainless steel binges & looks with the light of the looks with stainless steel binges & looks with the light of the looks with the looks with the light of the looks with the looks | 470 | Sqft. |     |      |
| I I I I I I I I I I I I I I I I I I I | P&F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light littings, taping and finished to proper line & level including making croves and trap doors for A.C. Unit in 18 mm thick M.R. Grade playwood with stainless steel hinges & locks with molding 1" x 1" or edges, if any including finishing with white plastics.   | 470 | Sqft. |     |      |
| I I I I I I I I I I I I I I I I I I I | PALSE CEILING (at 8'-6" high)  P& F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making roves and trap doors for A.C. Unit in 18 mm thick M.R. Grade allywood with stainless steel hinges & locks with molding 1" x 1" or edges, if any including finishing with white plastic emulsion aint etc. complete in all respects  | 470 | Sqft. |     |      |
| I I I I I I I I I I I I I I I I I I I | PALSE CEILING (at 8'-6" high)  2 & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light littings, taping and finished to proper line & level including making proves and trap doors for A.C. Unit in 18 mm thick M.R. Grade lywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion aint etc. complete in all respects.  Note: - Only the plan area will be measured for payment Ne  | 470 | Sqft. |     |      |
| 1                                     | PALSE CEILING (at 8'-6" high)  2 & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light littings, taping and finished to proper line & level including making proves and trap doors for A.C. Unit in 18 mm thick M.R. Grade lywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion aint etc. complete in all respects.  Note: - Only the plan area will be measured for payment. No extra ayment will be made for cutouts groover moldings.   | 470 | Sqft. |     |      |
| I I I I I I I I I I I I I I I I I I I | PALSE CEILING (at 8'-6" high)  P& F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making roves and trap doors for A.C. Unit in 18 mm thick M.R. Grade allywood with stainless steel hinges & locks with molding 1" x 1" or edges, if any including finishing with white plastic emulsion aint etc. complete in all respects  | 470 | Sqft. |     |      |

当

| 10. | PANELING   | 750 | Sqft. |      |   |
|-----|--|-----|-------|------|---|
|     | PVC Paneling ( Gold Di Heavy )                                       |     |       |      |   |
|     | Ivory & burgundy color with border As per Architect design           |     |       |      |   |
| 11. | VOUCHER STAND  | 1   | No    |      |   |
|     | Voucher stand of size 4'-0"x 3'-0" x 1'-0" made of 19 mm Anti-       |     |       |      |   |
|     | termite commercial board. All exterior surfaces shall have 1mm       |     |       |      |   |
|     | thick laminate including partition boxes. It shall have 5 partitions |     |       | 4    |   |
|     | for keeping vouchers. All edges shall have teak wood margin          |     |       |      |   |
|     | molding with duly polished in burgundy color (Bank Shade).           |     |       |      | A |
| 12. | NOTICE BOARD   | 1   | No    |      |   |
|     | Notice board of size 4'-0" x 2'-0" made of 19 mm anti termite        |     |       |      |   |
|     | commercial board at back. Board shall be covered with 12 mm thick    |     |       |      |   |
|     | celotexee board & matty fabric of burgundy color. Front & all side   |     |       |      |   |
|     | shall be covered with 1mm thick laminate. All edges shall be         |     |       |      |   |
|     | covered with teak wood margin/ molding and duly polished             |     |       |      |   |
|     | burgundy (Bank Shade).   |     |       |      |   |
| 13. | SUGGESTION BOX   | 1   | No.   |      |   |
|     | Suggestion box of size 1'-0" x 1'-0" x 9" made of 19mm thick         |     |       |      |   |
|     | commercial board. All exposed surfaces shall be covered with 1mm     |     |       | = 11 |   |
|     | thick laminate of white cedar color. Edges Shall be covered with     |     |       |      |   |
|     | teak wood margin/ molding. It shall be polished in burgundy color    |     |       |      |   |
|     | (Bank color). A slit opening of 10 mm 22150mm is o be provided at    |     |       | -    |   |
|     | the top of the box an open able shutter made of 19mm thick drop      |     |       |      |   |
|     | board is to be provided. Proper arrangement for locks shall be made  |     |       |      |   |
|     | by the contractor.   |     |       |      |   |
| 14. | STEEL SETTEE   | 2   | No.   |      |   |
|     | Providing of three Seater silver color steel settee.                 |     |       |      |   |
| 15. | SIDE TABLE (2'-0" x 2'-0")   | 1   | No.   |      |   |
|     | S/F keeping in position side table made out of 3/4" commercial       |     |       |      |   |
|     | board, CP T/Wd rigid framing 1.5" X 1.5" size wood. The table top    |     |       |      |   |
|     | shall be of 3/4" thick block board and in mica laminate 1.0          |     |       |      |   |
|     | mm thick of bank shade. All wood works shall be wax/spirit           |     |       |      |   |
|     | polished over a coat of Linseed oil finish.                          |     |       |      |   |
| 16. | CENTRAL TABLE (3'-0" x 1'-6")  | 11  | No.   |      |   |
|     | Supplying of centre table of size 3'-0" X 1'-6" with 12 mm thick     |     |       |      |   |
|     | glass on top   |     |       |      |   |
| 17. | CUPBOARDS ON STRONG ROOM, STATIONERY ROOM                            | 150 | Sqft. |      |   |
|     | &  |     |       |      |   |
|     | UPS ROOM   |     |       |      |   |
|     | P & s Cupboards made of 19, thick laminated ply on panel inside &    |     |       |      |   |
|     | outside. Inside ply shall also be covered with lamination as per     |     |       |      |   |
|     | design. Work include all accessories like locks, handles, hinges etc |     |       |      |   |
|     | TOTAL  |     |       |      |   |
|     | GST (18 %)   |     |       |      |   |
|     | GRAND TOTAL  |     |       |      |   |

也会