FINANCIAL BID FOR FURNISHING WORK						
PUNJAB GRAMIN BANK, BRANCH - BHINDRAN, DISTT SANGRUR						
S. No.	Description of items	Qty	Unit	Rate	Amount	
				(In Rs.)	(In Rs.)	
1.	CLERICAL COUNTER	41/2'	Rft.			
	P & F Clerical Counter 4'-6" x 2'-6"X 2'-6" Ht. with 12" high, 12	- /2	7444			
	mm thick glass on front with required wooden/aluminums					
	supports. Counter shall have wooden partition 4'-0"x4'-0" with					
	both side 1 mm thick laminate & teak wood molding & all					
	around duly polished on one side of counter. Counter shall be					
	made of 19 mm thick commercial board of Duro / Century/ kit					
	ply. It shall be finished with 1 mm thick laminate of <b>CEDAR WHITE</b> color on all sides of counter. The rates also include			20		
	drawer with Hettich ball bearing slides, cabinet box etc.					
	Counters are to be provided with computer keyboard tray of					
	Ebco make code no KBT 45 and drawers and boxes also making					
	position for electrical points conduits & switch boxes with					
	plastic round shape 2" diameter openings etc also fitting of U.P.S					
	shelf, foot rest of 3" x 1.5" in C.P. teak wood at the bottom. I.e.					
	complete job in all respects with fitting and accessories like					
	Godrej locks, handles, hinges etc. Lower portion 4" wide shall be					
	in burgundy color laminate (Bank shade) on front and side.					
	Edges of the counter shall have teak wood molding duly					
	polished. Edges shall be covered with teak wood molding/margin duly burgundy color (Bank color) polished.					
2.	OFFICER TABLE WITH SIDE RACK	4'-6"	Rft.			
	(4'-6"x 2'-6", Side Rack- 3'-3" x 1'-3")	4-0	KIL.			
	P & F Officer Table 5'-0" x 2'-6"X 2'-6" Ht. with 12" high, 12 mm					
	thick glass on front with required wooden/aluminums supports.					
	work includes side rack 3'-6" x 1'-6" x 2'-0". Table & side rack					
	shall be made with 19 mm thick commercial board of Duro /					
	Century/ kit ply. It shall be finished with 1 mm thick laminate of					
	CEDAR WHITE color on all sides of counter. The rates also					
	include drawer with Hettich ball bearing slides, cabinet box etc.					
	Counters are to be provided with computer keyboard tray of					
	Ebco make code no KBT 45 and drawers and boxes also making position for electrical points conduits & switch boxes with					
	plastic round shape 2" diameter openings etc also fitting of U.P.S					
	shelf, <b>foot rest of 3" x 1.5" in C.P. teak wood</b> at the bottom. I.e.					
	complete job in all respects with fitting and accessories like					
	Godrej locks, handles, hinges etc. Lower portion 4" wide shall be					
	in burgundy color laminate (Bank shade) on front and side.					
	Edges of the counter shall have teak wood molding duly					
	polished. Edges shall be covered with teak wood					
3.	molding/margin duly burgundy color (Bank color) polished.	(1.0"	D.C.			
3.	CASHIER COUNTER (With Door Closer) Providing and fixing of CASHIER counter 6'-0" x 2'-6" wide, 3'-9"	6'-0"	Rft.			
	high shall be made of 19 mm. thick commercial board of Duro/					
	Century/kit ply and finished with 1mm. <b>CEDAR WHITE</b> color					
	laminate on all vertical & exposed and visible surfaces of				A.	
	counter. Counters are to be provided with computer keyboard			Į.		
	tray of Ebco make code no KBT 45 and drawers with hettich ball					
	bearing slides for drawer slides with partition for keeping					
	currency and boxes. Also marking position for electrical points					
	conduits & switch boxes with plastic round shape 2" diameter					
	openings etc also fitting of U.P.S. shelf at bottom, i.e. complete					
	job in all respects with fittings and accessories like godrej locks,					
	handles, hinges etc. Lower portion 4" wide shall be in burgundy					
	color laminate (Bank shade) on front and side. Edges of the counter shall have teak wood molding duly polished.					

4.					
т.	MANAGER TABLE 6'-0" X 2'-6" with side rack & Back rack	1	Nos.		
		1	1403.	-	
,	Manager Table 6'-0" x 2'-6" x 2'-6" with side rack of size 3'-6" X				
	1'-6", 2'-6" high. It shall be made of 19 mm thick anti termite				
	commercial board/ Bishop Board. Top and vertical - exposed				
	surfaces shall have 1mm. thick WHITE CEDAR laminate				
	matching with existing table all exposed edges shall have teak				
	wood molding duly polished. Lower portion 4" wide shall be in				
	burgundy color laminate (Bank shade) on front and side. The				
	rate also includes fitting of lockable keyboards, locks in drawers				
	with Hettich ball bearing slides, terminals & C.P.U Shelf, foot rest				
	of size 3" x 1.5". The non sun mica area should be duly painted			1	
	or polished after making the smooth ground with second quality				
	paint and chalk mittii I.e. Complete job in all respects.				
5.	MANAGER TABLE - TOP GLASS	1	Nos.		
J.		_	11001		
	6'-0" X 2'-6" x 8 MM with Grinding of Edges & Corners.				
6.	OFFICER TABLE - TOP GLASS	1	Nos.		
0.		-	11001		
	4'-6" X 2'-6" x 8 MM with Grinding of Edges & Corners.				
7.	ALUMINIUM PARTITION				
, .		445	0.0		
	CASHIER CABIN 7' HT.	115	Sqft.		
	Aluminum section shall be 4" x 1.75" x 2 mm ivory color powder				
	coated. Partition shall have 8 mm thick glass on front & sides.		000		
	Upper Portion 3'-6" ht. shall have 8 mm thick glass & 8 mm	-0	Daniel Con	3	
	powder coated jaali on walls. Front of the cabin shall have	80	यामाक	8	
		JA.		D. C.	
	horizontal gap of 2" width at the front so that customer &	AP &	GAR	SAD	
	cashier can listen to each other. Lower 3'-6" Ht. Portion shall	*	8 8	*R	
	The state of the s	200	The state of the s	F.R	
	have pre -laminated board / Bison Board Ivory color fixed in	0 3	-	55	
	aluminum frame matching with the Ivory color lamination. Roof	9.0	TO RUM DE	20	
		9	यालय,	P	
	of the cashier cabin shall also have 8 mm thick powder coated		0000		
	jali. The rates also include fixing of stoppers, handles, hinges;				
	door closer & Goderaj lock to the cashier door etc complete job				
	in all respects.				
	MANAGER CABIN PARTITION 5'-0" HT.	75	Sqft.		
		73	Sqrt.		
	P & F Manager Cabin Partition of aluminum 5'-0" Ht. of 4" x				
	1.75" x 2 mm ivory color powder coated pipe. Lower Portion 3'-				
	6" Ht. shall have pre -laminated board / Bison Board Ivory color				
	fixed in aluminum frame matching with the Ivory color				
	lamination. Upper portion of the partition shall have 6 mm thick				
	glass. The rates include u shaped neoprene gasket.				
-		120	Sqft.		
0		130	Sam.		
8.	MAIN ENTERANCE DOOR & BACK DOOR		oqia		
8.	The state of the s		Dqra		
8.	( With Lock & Door Closer )		oqia		
8.	( With Lock & Door Closer ) P & F of aluminum door 8' Ht high as per design. The aluminum		oqra		
8.	( With Lock & Door Closer ) P & F of aluminum door 8' Ht high as per design. The aluminum		Sqrt		
8.	(With Lock & Door Closer)  P & F of aluminum door 8' Ht high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be		Jqiu		
8.	(With Lock & Door Closer)  P & F of aluminum door 8' Ht high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of		Sqra		
8.	(With Lock & Door Closer)  P & F of aluminum door 8' Ht high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be		Sqra		
8.	(With Lock & Door Closer)  P & F of aluminum door 8' Ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in		Sqra		
8.	(With Lock & Door Closer)  P & F of aluminum door 8' Ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm		Sqra		
8.	(With Lock & Door Closer)  P & F of aluminum door 8' Ht high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre-laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading		Squa		
8.	(With Lock & Door Closer)  P & F of aluminum door 8' Ht high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre-laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading		Squa		
8.	(With Lock & Door Closer)  P & F of aluminum door 8' Ht high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting		Squa		
8.	(With Lock & Door Closer)  P & F of aluminum door 8' Ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles,		Squa		
8.	(With Lock & Door Closer)  P & F of aluminum door 8' Ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles,		Squa		
	(With Lock & Door Closer)  P & F of aluminum door 8' Ht high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects.	530			
	(With Lock & Door Closer)  P & F of aluminum door 8' Ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects.  FALSE CEILING (at 8'-6" high)	530	Sqft.		
	(With Lock & Door Closer)  P & F of aluminum door 8' Ht high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects.	530			
	(With Lock & Door Closer)  P & F of aluminum door 8' Ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects.  FALSE CEILING (at 8'-6" high)  P & F in position false ceiling in Armstrong 600 X 600 mm x	530			
	(With Lock & Door Closer)  P & F of aluminum door 8' Ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects.  FALSE CEILING (at 8'-6" high)  P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by	530			
	(With Lock & Door Closer)  P & F of aluminum door 8' Ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects.  FALSE CEILING (at 8'-6" high)  P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making	530			
	(With Lock & Door Closer)  P & F of aluminum door 8' Ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects.  FALSE CEILING (at 8'-6" high)  P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making	530			
	(With Lock & Door Closer)  P & F of aluminum door 8' Ht high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects.  FALSE CEILING (at 8'-6" high)  P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts	530			
	(With Lock & Door Closer)  P & F of aluminum door 8' Ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects.  FALSE CEILING (at 8'-6" high)  P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line	530			
	(With Lock & Door Closer)  P & F of aluminum door 8' Ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects.  FALSE CEILING (at 8'-6" high)  P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line	530			
	(With Lock & Door Closer)  P & F of aluminum door 8' Ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects.  FALSE CEILING (at 8'-6" high)  P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in	530			
9.	(With Lock & Door Closer)  P & F of aluminum door 8' Ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects.  FALSE CEILING (at 8'-6" high)  P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges &	530			
	(With Lock & Door Closer)  P & F of aluminum door 8' Ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects.  FALSE CEILING (at 8'-6" high)  P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in	530			
	(With Lock & Door Closer)  P & F of aluminum door 8' Ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects.  FALSE CEILING (at 8'-6" high)  P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing	530			
9.	(With Lock & Door Closer)  P & F of aluminum door 8' Ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects.  FALSE CEILING (at 8'-6" high)  P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects.	530			
	(With Lock & Door Closer)  P & F of aluminum door 8' Ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects.  FALSE CEILING (at 8'-6" high)  P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing	530			
	(With Lock & Door Closer)  P & F of aluminum door 8' Ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects.  FALSE CEILING (at 8'-6" high)  P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No	530			
	P & F of aluminum door 8' Ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects.  FALSE CEILING (at 8'-6" high)  P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings,	530			
	(With Lock & Door Closer)  P & F of aluminum door 8' Ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects.  FALSE CEILING (at 8'-6" high)  P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No	530			
9.	P & F of aluminum door 8' Ht high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects.  FALSE CEILING (at 8'-6" high)  P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects.  (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any type of design etc.)		Sqft.		
9.	(With Lock & Door Closer)  P & F of aluminum door 8' Ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects.  FALSE CEILING (at 8'-6" high)  P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects.  (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any type of design etc.)  PANELING	530 750			
	P & F of aluminum door 8' Ht high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects.  FALSE CEILING (at 8'-6" high)  P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects.  (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any type of design etc.)		Sqft.		

11.	STORAGE CABINET ( 10 X 3'-6" X 1'-3" ) (1 CABINET )	20	Caft		
11.	Providing and fixing in position modular wooden storage	20	Sqft.		
	cabinets along with partitions having 4'-0" ht. and 1'-6" depth				
	and 3'-6" width etc. It shall be made out of 25.0 mm thick				
	commercial board with 1.0mm thick laminate (white cedar) on				
	all exposed surface and 1.0 mm thick laminate (burgundy) on				
	skirting. The shutters shall have CAM locks, handles, auto				
	closing hinges, magnate tic catchers etc. of approved make. All				
	the exposed edges of commercial board shall be concealed with				
	2.0 mm PVC edges binding; The internal surface shall be				
	finished with French spirit polish All complete to the				
	satisfaction of the architect. 4'-0" x 3'-6", Depth - 1'-6".				
12.	VOUCHER STAND	1	No		
1	Voucher stand of size 4'-0"x 3'-0" x 1'-0" made of 19 mm Anti-		110		
	termite commercial board. All exterior surfaces shall have 1mm				
	thick laminate including partition boxes. It shall have 5				
	partitions for keeping vouchers. All edges shall have teak wood			8	
	margin molding with duly polished in burgundy color (Bank				
	Shade).				
13.	NOTICE BOARD	1	No		
201	Notice board of size 4'-0" x 2'-0" made of 19 mm anti termite				
	commercial board at back. Board shall be covered with 12 mm				
	thick celotexee board & matty fabric of burgundy color. Front &	10			
	all side shall be covered with 1mm thick laminate. All edges				
	shall be covered with teak wood margin/ molding and duly			4	
	polished burgundy (Bank Shade).				
14.	SUGGESTION BOX	1	No.		
	Suggestion box of size 1'-0" x 1'-0" x 9" made of 19mm thick		-000-		
	commercial board. All exposed surfaces shall be covered with	2	ग्रामी	5	
	1mm thick laminate of white cedar color. Edges Shall be covered	7.5		S.B	
	with teak wood margin/ molding. It shall be polished in	AP I	300	ey B	6
	burgundy color (Bank color). A slit opening of 10 mm 22150mm	de si	1	EB	
	is o be provided at the top of the box an open able shutter made	Sign	Care de la constante de la con	P	
	of 19mm thick drop board is to be provided. Proper	8	श्लिय की	7	
	arrangement for locks shall be made by the contractor.		0000		
15.	SIDE TABLE (2'-0" x 2'-0")	1	No.		
	S/F keeping in position side table made out of 3/4" commercial				
	board, CP T/Wd rigid framing 1.5" X 1.5" size wood. The table		2		
	top shall be of 3/4" thick block board and in mica laminate 1.0				
	mm thick of bank shade. All wood works shall be wax/spirit				
	polished over a coat of Linseed oil finish.				
16.	CUPBOARDS ON STRONG ROOM, STATIONARY ROOM &	130	Sqft.		
	UPS ROOM				
	P & s Cupboards made of 19, thick laminated ply on panel inside				
	& outside. Inside ply shall also be covered with lamination as				
	per design. Work include all accessories like locks, handles ,	2.			
	hinges etc				
	TOTAL				
	GST (18 %)				
	GRAND TOTAL				
	GIGHT LOTTIN				

## **Total in Words:**