3	8	in the second		Al	nnexure-10-A
19 N 8	FINANCIAL BID FOR FURNISHIN	NG WO	RK		
3/7 3	PUNJAB GRAMIN BANK, BRANCH:- LEHF	RAGAGA	, SANG	RUR	
S.No.	Description of items	Qty	Unit	Rate	Amount
TO A				(In Rs.)	(In Rs.)
1	CLEDICAL COUNTED	4'-6"	Rft.		
1.	CLERICAL COUNTER D. S. F. Clarical Counter 4: 6" v. 2' 6"V 2' 6" Ut. with 12" high 12	4 -0	Kit.		
	P & F Clerical Counter 4'-6" x 2'-6"X 2'-6" Ht. with 12" high, 12 mm thick glass on front with required wooden/aluminums supports. Counter shall have wooden partition 4'-0"x4'-0" with both side 1 mm thick laminate & teak wood molding & all around duly polished on one side of counter. Counter shall be made of 19 mm thick commercial board of Duro / Century/ kit ply. It shall be finished with 1 mm thick laminate of CEDAR WHITE color on all sides of counter. The rates also include drawer with Hettich ball bearing slides, cabinet box etc. Counters are to be provided with computer keyboard tray of Ebco make code no KBT 45 and drawers and boxes also making position for electrical points conduits & switch boxes with plastic round shape 2" diameter openings etc also fitting of U.P.S shelf, foot rest of 3" x 1.5" in C.P. teak wood at the bottom. I.e. complete job in all respects with fitting and accessories like Godrej locks, handles, hinges etc. Lower portion 4" wide shall be in burgundy color laminate (Bank shade) on front and side. Edges of the counter shall have teak wood molding duly polished. Edges shall be covered with teak wood molding/margin				
2.	duly burgundy color (Bank color) polished. OFFICER TABLE	9'-0"	Rft.	19	
	(4'-6"x 2'-6") No's - 2	171 270	100100000		
	P & F Officer Table 4'-6" x 2'-6"X 2'-6" Ht. with 12" high, 12 mm thick glass on front with required wooden/aluminums supports. work with 19 mm thick commercial board of Duro / Century/ kit ply. It shall be finished with 1 mm thick laminate of CEDAR WHITE color on all sides of counter. The rates also include drawer with Hettich ball bearing slides, cabinet box etc. Counters are to be provided with computer keyboard tray of Ebco make code no KBT 45 and drawers and boxes also making position for electrical points conduits & switch boxes with plastic round shape 2" diameter openings etc also fitting of U.P.S shelf, foot rest of 3" x 1.5" in C.P. teak wood at the bottom. I.e. complete job in all respects with fitting and accessories like Godrej locks, handles, hinges etc. Lower portion 4" wide shall be in burgundy color laminate (Bank shade) on front and side. Edges of the counter shall have teak wood molding duly polished. Edges shall be covered with teak wood molding/margin duly burgundy color (Bank color) polished.				
3.	CASHIER COUNTER	6'-0"	Rft.		
	Providing and fixing of CASHIER counter 6'-0" x 2'-6" wide, 3'-9" high shall be made of 19 mm. thick commercial board of Duro/ Century/kit ply and finished with 1mm. CEDAR WHITE color laminate on all vertical & exposed and visible surfaces of counter. Counters are to be provided with computer keyboard tray of Ebco make code no KBT 45 and drawers with hettich ball bearing slides for drawer slides with partition for keeping currency and boxes. Also marking position for electrical points conduits & switch boxes with plastic round shape 2" diameter openings etc also fitting of U.P.S. shelf at bottom, i.e. complete job in all respects with fittings and accessories like godrej locks, handles, hinges etc. Lower portion 4" wide shall be in burgundy color laminate (Bank shade) on front and side. Edges of the counter shall have teak wood molding duly polished.			â	

Manager Table 6-0" x 2'-6" with side rack of size 3'-6" X 1-6" yellow that all be made of 19 mm thick anti-termite commercial board. Bishop Board. Top and vertical — exposed surfaces shall have lumn, thick WHITE CEDAR laminate matching with existing table all exposed edges shall have teak wood moleding duly polished. Lower portion a' wide shall be in burgundy color laminate (Bank shade) on front and side. The rate also includes fitting of lockable keyboards, locks in drawers with Hettich hall bearing slides, terminals & C.P.IJ Shelf, foot rest of size 3" x 1.5". The non sun mica area should be duly painted or polished after making the smooth ground with second quality paint and chalk mittil Le. Complete job in all respects. 5. MANAGER TABLE — TOP GLASS (No's - 1 4'-6" X 2'-6" x 8 mm with Grinding of Edges & Corners. 6. OFFICER TABLE — TOP GLASS (No's - 1 1 Nos. 4'-6" X 2'-6" x 8 mm with Grinding of Edges & Corners. 7. ALUMINIUM PARTITION CASHIER CABIN 7" HT. Aluminum section shall be 4" x 1.75" x 2 mm ivory color powder coated. Partition shall have 8 mm thick glass on front & sides. Upper Portion 3'-6" ht. shall have 8 mm thick glass & 8 mm powder coated jaali on walls. Front of the cabin shall have horizontal gap of 2" width at the front so that customer & cashier can listen to each other. Lower 3'-6" Ht. Portion shall have pre-laminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color board to prove conted jali. The rates also include fixing of stoppers, handles, hinges; door closer & Goderaj lock to the cashier door et ecomplete job in all respects. MANAGER CABIN PARTITION S-0" HT. P & F Manager Cabin Partition of aluminum 3'-0" Ht. of 4" x 1.75" x 2 mm ivory color powder coated jiel. Lower Portion 3'-6" Ht. shall have pre-laminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color fixed in aluminum match to a shaped neoprene gasket. Is a shaped neoprene gasket. Is complete job in all respects. 8. MAIN ENTERNICE DOOR & BACK DOOR	4	MANAGED TABLE GLOWN ALTO				
1-6°, 2-6° high. It shall be made of 19 mm thick anti termite commercial board Bishop Board. Top and vertical — exposed surfaces shall have Imm. thick WHITE CEDAR Imminate management of the properties of the pr	4.	MANAGER TABLE 6'-0" X 2'-6" with side rack	1	Nos.		
commercial board. Bishop Board. Top and vertical — exposed surfaces shall have Imm. thick WIITE CEDAR laminate matching with existing table all exposed edges shall have teak wood molding duly polished. Lower portion A" wide shall be in burgundy color laminate (Bank shade) on front and side. The rate also includes fitting of lockable keyboards, locks in drawers with Hettich ball bearing slides, terminals & C.P.II Shief, foot rest of size 3" x 1.5". The non sum face area should be duly painted or polished after making the smooth ground with second quality paint and chalk mittil i.e. Complete job in all respects. 5. MANAGER TABLE — TOP GLASS /No's - 1 7. ALUMINIUM PARTITION CASHIER CABIN ? HT. 7. ALUMINIUM PARTITION CASHIER CABIN ? HT. Aluminum section shall be 4" x 1.75" x 2 mm ivory color powder coated. Partition shall have 8 mm thick glass on front & sides. Upper Portion 3"-6" ht. shall have 8 mm thick glass & 8 mm powder coated jaali on walls. Front of the cabin shall have borizontal agap of 2" width at the front so that customer & cashier can listen to each other. Lower 3"-6" Ht. Portion shall have pre-laminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color fixed in aluminum frame matching with the lower coated jail. The rates also include fixing of stoppers, handles, hinges; door closer & Goderaj locks to the cashier door etc complete job in all respects. MANAGER CABIN PARTITION S"-0" HT. P & F Manager Cabin Partition of aluminum 3"-0" Ht. of 4" x 1.75" x 2 mm ivory color powder coated jail. The rates also include this provided to the cashier door closer & Goderaj locks to the cashier door etc complete job in all respects. MANAGER CABIN PARTITIONS S"-0" HT. P & F Manager Cabin Partition of aluminum 3"-0" Ht. of 4" x 1.75" x 2 mm ivory color powder coated jail. The rates also include this provided the state of the cashier door allowed th	2	1' 6" 2' 6" high It shall be a consider ack of size 3'-6" X				
surfaces shall have Imm. thick WHITE CEDAR laminate matching with existing table all exposed edges shall have teak wood molding duly polished. Lower portion 4" wide shall be in burgundy color laminate (Bank shade) on front and side. The rate also includes fitting of lockable keyboards, locks in drawers with Hettich ball bearing slides, terminals & C.P.U. Shelf, floor rest of size 3" x 1.5". The non sun mica area should be duly painted or polished after making the smooth ground with second quality paint and chalk mittil Le. Complete job in all respects. 5. MANAGER TABLE — TOP GLASS / No's - 1 4.6" N. 2"-6" x 8 mm with Grinding of Edges & Corners. 6. OFFICER TABLE — TOP GLASS / No's - 1 4.6" X. 2"-6" x 8 mm with Grinding of Edges & Corners. 7. ALUMINIUM PARTITION CASHIR CABIN 7 IIT. Aluminum section shall be 4" x 1.75" x 2 mm ivory color powder coated. Partition shall have 8 mm thick glass on front & sides. Upper Portion 3"-6" ht. shall have 8 mm thick glass & 8 mm powder coated jain on walls. Front of the cabin shall have horizontal gap of 2" width at the front so that customer & cashier cabin shall also have 8 mm thick powder coated jain. The rates also include fixing of stoppers, handles, hinges; door closer & Goderaj lock to the cashier doer et complete job in all respects. MANNGER CABIN PARTITION 5"-0" HT. P & F Manager Cabin Partition of aluminum 5"-0" Ht. of 4" x 1.75" x 2 mm ivory color powder coated plic. Hower Portion 3"-6" Ht. shall have pre — laminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color lamination. Upper portion of the partition shall have for mm thick glass. The rates also include u shaped neoprene gasket. 8. MAIN ENTERNCE DOOR & BACK DOOR (With Lock & Door Closer) P & F of aluminum door 8" ht. high as per design. The aluminum scenario should be 4"x 1.75" x 2 mm for frame & panel shall be tory color. Upper part shall have 6 mm thick glass. The rates include u shaped neoprene gasket. 8. MAIN ENTERNCE DOOR & BACK DOOR (With Lock & Door Cl	300	1 -0, 2 -6 nigh. It shall be made of 19 mm thick anti termite				
matching with existing table all exposed edges shall have teak wood molding duly polished. Lower portion a" wide shall be in burgundy color laminate (Bank shade) on front and side. The rate also includes fitting of lockable keyboards, locks in drawers with Hettich ball bearing slides, terminals & C.P.U Shelf, foot rest of size 3" x 1.5". The non sun mica area should be duly painted or polished after making the smooth ground with second quality paint and chalk mittil Le. Complete jobin all respects. 5. MANAGER TABLE - TOP GLASS 6. G-G** X 2-6* x 8 mm with Grinding of Edges & Corners. 7. ALDMINION PARTITION CASHIER CABIN 7* HT. Aluminum section shall be 4" x 1.75" x 2 mm ivory color powder coated, Partition shall have 8 mm thick glass on front & sides. Upper Portion 3"-6" ht. shall have 8 mm thick glass & 8 mm powder coated jaal on walls. Front of the cabin shall have predaminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color lamination. Roof of the cashier can listen to each other. Lower 3'-6" Ht. Portion shall have predaminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color lamination. Roof of the cashier door late of the cashier door of the complex of the cashier door of the	Jan J	commercial board, Bishop Board, Top and vertical – exposed				
color laminate (Bank shade) on front and side. The rate also includes fitting of lockable keyboards, locks in drawers with Hettich ball bearing slides, terminals & C.P.U. Shelf, foot rest of size 3" x 1.5". The non sun mice area should be duly painted or polished after making the smooth ground with second quality paint and chalk mittil Le. Complete job in all respects. 5. MANNGER TABLE – TOP GLASS 6-0" X 2"-6" x 8 mm with Grinding of Edges & Corners. 6. OFFICER TABLE – TOP GLASS No's - 1 4"-6" X 2"-6" x 8 mm with Grinding of Edges & Corners. 7. ALUMINIUM PARTITION CASHIER CABIN 7" IIT. Aluminum section shall be 4" x 1.75" x 2 mm ivory color powder coated, Partition shall have 8 mm thick glass on front & sides. Upper Portion 3"-6" ht. shall have 8 mm thick glass on front & sides. Upper Portion 3"-6" ht. shall have 8 mm thick glass & B mm powder coated jail on walls. Front of the cashin shall have borizontal gap of 2" width at the front so that customer & eashier can liste to each other. Lower 3"-6" ht. Portion shall have pre—laminated board / Bison Board Ivory color fixed in aluminum frame matching with the lovry color lamination. Roof of the cashier cabin shall last on ave 8 mm thick power coated jail. The rates also include fixing of stoppers, handles, hinges; door closer & Goderaj lock to the cashier door etc complete job in all respects. MANNGER CABIN PARTITION \$"0" IIT. P & F Manager Cabin Partition of aluminum 5"0" Ht. of 4" x 1.75" x 2 mm ivory color powder coated pipe. Lower Portion 3"-6" Ht. shall have pre—laminated board / Bison Board Ivory color fixed in aluminum frame matching with the lovy color lamination. Upper portion of the partition shall have for mm thick glass. The rates include u shaped neoprene gasket. 8. MAIN ENTRANCE DOOR & BACK DOOR (With Lock & Door Cliseer) P & F of aluminum frame of ivory color. Upper part shall have 6 mm thick glass. The rates include u shaped neoprene gasket. Rates includes providing & fitting of all hardware tiems such as Goder joles, stoppers, handles,	国到以	surfaces shall have 1mm, thick WHITE CEDAR laminate				
color laminate (Bank shade) on front and side. The rate also includes fitting of lockable keyboards, locks in drawers with Hettich ball bearing slides, terminals & C.P.U Shelf, foot rest of size 3" x 1.5". The non sun mice area should be duly painted or polished after making the smooth ground with second quality paint and chalk mittil Le. Complete job in all respects. 5. MANAGER TABLE — TOP GLASS 6. OF YECRET TABLE — TOP GLASS / No's - 1 4 '-6" X 2'-6" x 8 mm with Grinding of Edges & Corners. 7. ALUMINUM PARTITION CASHIER CABIN 7' HT. Aluminum section shall be 4" x 1.75" x 2 mm ivory color powder coated. Partition shall have 8 mm thick glass on front & sides. Upper Portion 3'-6" ht. shall have 8 mm thick glass 8 mm powder coated jaali on walls. Front of the cabin shall have borizontal gap of 2" width at the front so that customer & cashier can listen to each other. Lower 3'-6" Ht. Portion shall have perlaminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color lamination. Roof of the cashier cabin shall also have 8 mm thick powder coated jali. The rates also include fixing of stoppers, handles, hingse; door closer & Goderaj lock to the cashier door etc complete job in all respects. MANAGER CABIN PARTITION S-0" HT. P & F Manager Cabin Partition of aluminum 5'-0" Ht. of 4" x 1.75" x 2 mm ivory color powder coated pipe. Lower Portion 3'-6" Ht. shall have pre-laminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color lamination. Upper portion of the partition shall have 6 mm thick glass. The rates include u shaped neoprene gasket. 8. MANN ENTERANCE DOOR & BACK DOOR (With Lock & Door Closer) P & F of aluminum door 8' ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be viory colored powder coated. The loudes channels, door loser, hinges ctc., i.e. Complete job in all respects. 9. FALSE CELLING (at 9-0" high) P & F of aluminum for any of the control of the door shall have pre- laminated	11 *B	matching with existing table all exposed edges shall have teak wood				
includes fitting of lockable keyboards, locks in drawers with Hettich ball bearing slides, terminals & C.P.U. Shelf, foot rest of size 3" x 1.5". The non sun mice area should be duly painted or polished after making the smooth ground with second quality paint and chalk mittil Le. Complete job in all respects. 5. MANAGER TABLE – TOP GLASS 6-6" X 2-6" x 8 mm with Grinding of Edges & Corners. 6. OFFICER TABLE – TOP GLASS / No's - 1 4 -6" x 2-6" x 8 mm with Grinding of Edges & Corners. 7. ALUMINIUM PARITTION CASHIRC CABN Y BT. Aluminum section shall be 4" x 1.75" x 2 mm ivory color powder coated. Partition shall have 8 mm thick glass on front & sides, Upper Portion 3"-6" ht. shall have 8 mm thick glass & 8 mm powder coated jaali on walls. Front of the cabin shall have preclaminated board / Bison Board Invo color fixed in aluminum frame matching with the Ivory color lamination. Roof of the cashier can listen to each other. Lower 3"-6" ltt. Portion shall have prelaminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color lamination. Roof of the cashier cabin shall also have 8 mm thick powder coated jali. The rates also include fixing of stoppers, handles, hinges; door closer & Goderaj lock to the cashier door etc complete job in all respects. MANAGER CABIN PARITTION S"-0" HT. P & F Manager Cabin Partition of aluminum 5"-0" ltt. of 4" x 1.75" x 2 mm ivory color prowder coated pipe. Lower Portion 3"-6" ltt. shall have pre-laminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color aluminum 5"-0" ltt. of 4" x 1.75" x 2 mm ivory color proveder coated. The lower 3"-0" high portion of the door shall have pre-laminated board / Bison Board Ivory color proper gasket. 8. MAIN ENTERANCE DOOR & BACK DOOR (With Lock & Door Closer) P & F of aluminum doors of the lower 3"-0" high portion of the door shall have pre-laminated board / Bison Board fixed in aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be viory colored powder coated. Th	ER	molding duly polished. Lower portion 4" wide shall be in burgundy				
ball bearing slides, terminals & C.P.U Shelf, foot rest of size 3" x 1.5". The non sun mice area should be duly painted or polished after making the smooth ground with second quality paint and chalk mittil Le. Complete job in all respects. 5. MANAGER TABLE — TOP GLASS 6. G-0" X 2"-6" x 8 mm with Grinding of Edges & Corners. 6. OFFICER TABLE — TOP GLASS / No"s - 1 2. ALDMINIUM PARTITION CASHIER CABIN 7" HT. Aluminum section shall be 4" x 1.75" x 2 mm ivory color powder coated. Partition shall have 8 mm thick glass on front & sides. Upper Portion 3"-6" ht. shall have 8 mm thick glass on front & sides. Upper Portion 3"-6" ht. shall have 8 mm thick glass & 8 mm powder coated jaali on walls. Front of the cabin shall have horizontal gap of 2" width at the front so that customer & cashier can listen to each other. Lower 3"-6" Ht. Portion shall have pre—laminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color lamination. Roof of the cashier cabin shall also have 8 mm thick powder coated jail. The rates also include fixing of stoppers, handles, hingse; door closer & Goderaj lock to the cashier door ete complete job in all respects. MANAGER CABIN PARTITION S"-0" HT. P & F Manager Cabin Partition of aluminum 5":0" Ht. of 4" x 1.75" x 2 mm ivory color powder coated pipe. Lower Portion 3"-6" Ht. shall have pre -laminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color lamination. Upper portion of the partition shall have 6 mm thick glass. The rates include u shaped neoprene gasket. 8. MANN ENTERANCE DOOR & BACK DOOR (With Lock & Door Closer) P & F of aluminum food of 8" ht. high as per design, The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be viory colored powder coated. The lower 3"-0" high portion of the door shall have pre-laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frame for ivory color. Upper partition for the door shall have pre-la	50	color laminate (Bank shade) on front and side. The rate also				
1.5". The non sun mica area should be duly painted or polished after making the smooth ground with second quality paint and chalk mittil Le. Complete job in all respects. 5. MANAGER TABLE — TOP GLASS 6-0" X 2"-6" x 8 mm with Grinding of Edges & Corners. 6. OFFICER TABLE — TOP GLASS / No's - 1	0	hall begins alides towning of OCKable Keyboards, locks in drawers with Hettich				
making the smooth ground with second quality paint and chalk mittil Le. Complete job in all respects. 5. MANAGER TABLE — TOP GLASS 1 Nos. 61-0" X 2"-6" x 8 mm with Grinding of Edges & Corners. 1 Nos. 4"-6" X 2"-6" x 8 mm with Grinding of Edges & Corners. 1 Nos. 4"-6" X 2"-6" x 8 mm with Grinding of Edges & Corners. 1 Nos. 4"-6" X 2"-6" x 8 mm with Grinding of Edges & Corners. 1 Nos. 4"-6" X 2"-6" x 8 mm with Grinding of Edges & Corners. 1 Nos. 4"-6" X 2"-6" x 8 mm with Grinding of Edges & Corners. 1 Nos. 4"-6" X 2"-6" x 8 mm with Grinding of Edges & Corners. 1 Nos. 4"-6" X 2"-6" x 8 mm with Grinding of Edges & Corners. 1 Nos. 4"-6" X 2"-6" x 8 mm with Grinding of Edges & Corners. 1 Nos. 4"-6" X 2"-6" x 8 mm with Grinding of Edges & Corners. 1 Nos. 4"-6" X 2"-6" x 8 mm with Grinding of Edges & Corners. 1 Nos. 4"-6" x 1.0" x 1.0		ball bearing stides, terminals & C.P.U Shelf, foot rest of size 3" x				
mittil Le. Complete job in all respects. 5. MANAGER TABLE — TOP GLASS 6-0" X 2-6" x 8 mm with Grinding of Edges & Corners. 6. OFFICER TABLE — TOP GLASS/No's - 1 4-6" X 2'-6" x 8 mm with Grinding of Edges & Corners. 7. ALUMINIUM PARTITION CASHIER CABIN 7: HT. Aluminum section shall be 4" x 1.75" x 2 mm ivory color powder coated. Partition shall have 8 mm thick glass on fromt & sides. Upper Portion 3'-6" ht. shall have 8 mm thick glass & 8 mm powder coated jaali on walls. Front of the cabin shall have horizontal gap of 2" width at the front so that customer & cashier can listen to each other. Lower 3'-6" Ht. Portion shall have pre— laminated board / Bison Board Ivoy color fixed in aluminum frame matching with the Ivory color lamination. Roof of the cashier eabin shall also have 8 mm thick powder coated jali. The rates also include fixing of stoppers, handles, hinges; door closer & Goderaj lock to the cashier door etc complete job in all respects. MANAGER CABIN PARTITION 5"-0" HT. P & F Manager Cabin Partition of aluminum 5'-0" Ht. of 4" x 1.75" x 2 mm ivory color powder coated pipe. Lower Portion 3'-6" Ht. shall have pre—laminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color lamination. Upper portion of the partition shall have 6 mm thick glass. The rates include ushaped neoprene gasket. 8. MAIN ENTERANCE DOOR & BACK DOOR (With Lock & Door Closer) P & F of aluminum door 8" ht. high as per design. The aluminum section should be 4" 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre—laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frame sincludes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., is. Complete job in all respects. 9. FALSE CEILING (at 9'-0" high) P & F in position false ceiling in Arms		1.3. The non sun mica area should be duly painted or polished after				
5. MANAGER TABLE—TOP GLASS 6-0° X 2-6° x 8 mm with Grinding of Edges & Corners. 6. OFFICER TABLE—TOP GLASS/No's - 1 4 -6° X 2'-6° x 8 mm with Grinding of Edges & Corners. 7. ALUMINIUM PARTITION CASHIER CABIN 7: HT. Aluminum section shall be 4° x 1.75° x 2 mm ivory color powder coated. Partition shall have 8 mm thick glass on front & sides. Upper Portion 3'-6° ht. shall have 8 mm thick glass & 8 mm powder coated jaali on walls. Front of the cabin shall have horizontal gap of 2° width at the front so that customer & eashier can listen to each other. Lover 3'-6° Ht. Portion shall have horizontal gap of 2° width at the front so that customer & eashier can listen to each other. Lover 3'-6° Ht. Portion shall have horizontal gap of 3's middle, hinges; door closer & Goderaj lock to the eashier door etc complete job in all respects. MANAGER CABIN PARTITION S-0° HT. P & F Manager Cabin Partition of aluminum 5'-0° Ht. of 4" x 1.75° x 2 mm ivory color powder coated pipe. Lower Portion 3'-6° Ht. shall have pre-laminated board / Bison Board flory color lamination. Upper portion of the partition shall have 6 mm thick glass. The rates include u shaped neoprene gasket. 8. MAIN ENTERANCE DOOR & BACK DOOR (With Lock & Door Closer) P & F of aluminum door 8' ht. high as per design. The aluminum section should be 4" x 1.75° x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre-laminated board / Bison Board fixed in aluminum frame of lovy color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. FALSE CEILING (at 9'-0" high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for full cutting. The provision		mittii la Complete in la la mittii la Complete in la la la mittii la Complete in la				
6. OFFICER TABLE TOP GLASS / No's - 1 4'-6" X 2'-6" x 8 mm with Grinding of Edges & Corners. 7. ALUMINIUM PARTITION CASHIER CABIN 7' HT. Aluminum section shall be 4" x 1.75" x 2 mm ivory color powder coated. Partition shall have 8 mm thick glass on front & sides. Upper Portion 3'-6" ht. shall have 8 mm thick glass on front & sides. Upper Portion 3'-6" ht. shall have 8 mm thick glass & 8 mm powder coated jaali on walls. Front of the cabin shall have horizontal gap of 2" width at the front so that customer & cashier can listen to each other. Lower 3'-6" Ht. Portion shall have prelaminated board / Bison Board livry color fixed in aluminum frame matching with the Ivory color lamination. Roof of the cashier cabin shall also have 8 mm thick powder coated jali. The rates also include fixing of stoppers, handles, hinges; door closer & Goderaj lock to the cashier door etc complete job in all respects. MANAGER CABIN PARTITION 5'-0" III. P & F Manager Cabin Partition of aluminum 5'-0" Ht. of 4" x 1.75" x 2 mm ivory color powder coated pipe. Lower Portion 3'-6" Ht. shall have pre -laminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color lamination. Upper portion of the partition shall have 6 mm thick glass. The rates include u shaped neoprene gasket. 8. MAIN ENTERANCE DOOR & BACK DOOR (With Lock & Door Closer) P & F of aluminum door 8" ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color; Upper part shall have 6 mm thick glass. These aluminum frame sincludes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Goderj locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. FALSE CELLING (at 9'-0" high) P & F in position false eciling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima	Ē					
6. OFFICER TABLE—TOP GLASS / No's - 1 4'-6'' X 2-6'' x 3 -6'' x 4 mm with Grinding of Edges & Corners. 7. ALUMINIUM PARTITION CASHIER CABIN 7' HT. Aluminum section shall be 4'' x 1.75'' x 2 mm ivory color powder coated. Partition shall bave 8 mm thick glass on front & sides. Upper Portion 3'-6'' ht. shall have 8 mm thick glass & 8 mm powder coated jaali on walls. Front of the cabin shall have horizontal gap of 2'' width at the front so that customer & cashier can listen to each other. Lower 3'-6'' Ht. Portion shall have prelaminated board / Bison Board Ivory color fixed in aluminum frame matching with the vory color lamination. Roof of the cashier cabin shall also have 8 mm thick powder coated jali. The rates also include fixing of stoppers, handles, hinges; door closer & Goderaj lock to the cashier door etc complete job in all respects. MANAGER CABIN PARTITION 5'-0" HT. P & F Manager Cabin Partition of aluminum 5'-0" Ht. of 4" x 1.75" x 2 mm ivory color powder coated pipe. Lower Portion 3'-6" Ht. shall have pre-laminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color lamination. Upper portion of the partition shall have 6 mm thick glass. The rates include u shaped neoprene gasket. 8. MAIN ENTERANCE DOOR & BACK DOOR (With Lock & Door Closer) P & F of aluminum door 8" ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre-laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Goderj locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. PALSE CELING (at 9'-9' high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme R19 9 Prima file as specified by Armstrong Co. with suspenders wh	5.		1	Nos.		
4'-6" X 2'-6" x 8 mm with Grinding of Edges & Corners. ALUMINIUM PARTITION CASHIER CABIN 7' HT. Aluminum section shall be 4" x 1.75" x 2 mm ivory color powder coated. Partition shall have 8 mm thick glass on front & sides. Upper Portion 3'-6" ht. shall have 8 mm thick glass & 8 mm powder coated jaal ion walls. Front of the cabin shall have horizontal gap of 2" width at the front so that customer & cashier can listen to each other. Lower 3'-6" Ht. Portion shall have prelaminated board / Bison Board flovry color fixed in aluminum frame matching with the Ivory color lamination. Roof of the cashier cabin shall also have 8 mm thick powder coated gial. The rates also include fixing of stoppers, handles, hinges; door closer & Goderaj lock to the cashier door ete complete job in all respects. MANAGER CABIN PARTITION 5'-0" HT. P & F Manager Cabin Partition of aluminum 5'-0" Ht. of 4" x 1.75" x 2 mm ivory color powder coated pipe. Lower Portion 3'-6" Ht. shall have pre laminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color famination. Upper portion of the partition shall have 6 mm thick glass. The rates include u shaped neoprene gasket. MAIN ENTERNACE DOOR & BACK DOOR (With Lock & Door Closer) P & F of aluminum door 8' ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frame includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Goderj locks, stoppers, handles, door closer, hinges cte., i.e. Complete job in all respects. P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for diffusers and light fittings, taping and finis		6'-0" X 2'-6" x 8 mm with Grinding of Edges & Corners.				
CASHER CABN 7: HT. Aluminum section shall be 4" x 1.75" x 2 mm ivory color powder coated. Partition shall have 8 mm thick glass on front & sides. Upper Portion 3"-6" ht. shall have 8 mm thick glass & 8 mm powder coated jaali on walls. Front of the cabin shall have borizontal gap of 2" width at the front so that customer & cashier can listen to each other. Lower 3'-6" Ht. Portion shall have perlaminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color lamination. Roof of the cashier cabin shall also have 8 mm thick powder coated jali. The rates also include fixing of stoppers, handles, hinges; door closer & Goderaj lock to the cashier door et complete job in all respects. MANAGER CABIN PARTITION 5"-0" HT. P & F Manager Cabin Partition of aluminum 5"-0" Ht. of 4" x 1.75" x 2 mm ivory color powder coated pipe. Lower Portion 3"-6" Ht. shall have pre-laminated board / Bison Board Ivory color lixed in aluminum frame matching with the Ivory color lamination. Upper portion of the partition shall have 6 mm thick glass. The rates include u shaped neoprene gasket. 8. MAIN ENTERANCE DOOR & BACK DOOR (With Lock & Door Closer) P & F of aluminum door 8" ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3"-0" high portion of the door shall have pre-laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum Irames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items seut as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. FALSE CEILING (at 9"-0" high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 m Dune Supreme RH 99 Prima file as specified by Armstrong Co, with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and f	6.		1	Nos.		
CASHIER CABIN 7: HT. Aluminum section shall be 4" x 1.75" x 2 mm ivory color powder coated. Partition shall have 8 mm thick glass on front & sides. Upper Portion 3'-6" ht. shall have 8 mm thick glass & 8 mm powder coated juali on walls. Front of the cabin shall have prelaminated board / Bison Board flory or color fixed in aluminum frame matching with the Ivory color lamination. Roof of the cashier cabin shall also have 8 mm thick powder coated juli. The rates also include fixing of stoppers, handles, hinges; door closer & Goderaj lock to the cashier door etc complete job in all respects. MANAGER CABIN PARTITION 5'-0" HT. P & F Manager Cabin Partition of aluminum 5'-0" Ht. of 4" x 1.75" x 2 mm ivory color powder coated pipe. Lower Portion 3'-6" Ht. shall have pre-laminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color lamination. Upper portion of the partition shall have 6 mm thick glass. The rates include u shaped neoprene gasket. 8. MAIN ENTERANCE DOOR & BACK DOOR (With Lock & Door Closer) P & F of aluminum door 8' ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. FALSE CEILING (at 9'-0" high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting, If any and necessary cutouts for diffusers and light littings, taping and finished to proper lime & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with	_					
Aluminum section shall be 4" x 1.75" x 2 mm ivory color powder coated. Partition shall have 8 mm thick glass on front & sides. Upper Portion 3"-6" ht. shall have 8 mm thick glass on front & sides. Upper Portion 3"-6" ht. shall have 8 mm thick glass & 8 mm powder coated jaali on walls. Front of the cabin shall have borizontal gap of 2" width at the front so that customer & cashier can listen to each other. Lower 3'-6" Ht. Portion shall have per laminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color lamination. Roof of the cashier cabin shall also have 8 mm thick powder coated jali. The rates also include fixing of stoppers, handles, hinges; door closer & Goderaj look to the cashier door etc complete job in all respects. MANAGER CABIN PARTITION 5"-0" IIT. P & F Manager Cabin Partition of aluminum 5"-0" Ht. of 4" x 1.75" x 2 mm ivory color powder coated pipe. Lower Portion 3'-6" Ht. shall have pre -laminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color lamination. Upper portion of the partition shall have 6 mm thick glass. The rates include u shaped neoprene gasket. 8. MAIN ENTERANCE DOOR & BACK DOOR (With Lock & Door Closer) P & F of aluminum door 8" ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3"-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. FALSE CELING (at 9"-0" high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting, If any and necessary c	7.				y company of	
Aluminum section shall be 4" x 1.75" x 2 mm ivory color powder coated. Partition shall have 8 mm thick glass & 8 mm powder coated jaali on walls. Front of the cabin shall have horizontal gap of 2" width at the front so that customer & cashier can listen to each other. Lower 3'-6" Ht. Portion shall have prelaminated board / Bison Board flory color lixed in aluminum frame matching with the Ivory color lamination. Roof of the eashier cabin shall also have 8 mm thick powder coated jali. The rates also include fixing of stoppers, handles, hinges; door closer & Goderaj lock to the eashier door etc complete job in all respects. MANAGER CABIN PARTITION 5'-0" HT. P & F Manager Cabin Partition of aluminum 5'-0" Ht. of 4" x 1.75" x 2 mm ivory color powder coated pipe. Lower Portion 3'-6" Ht. shall have pre-laminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color lamination. Upper portion of the partition shall have for mutick glass. The rates include u shaped neoprene gasket. 8. MAIN ENTERANCE DOOR & BACK DOOR (With Lock & Door Closer) P & F of aluminum door 8' ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Goderj locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. FALSE CEILING (at 9'-0" high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting, If any and necessary cutouts for diffusers and light fittings, taping and finished to proper lime & level including making groves and trap doors for A.C. Unit in 18		CASHIER CABIN 7' HT.	120	Sqft.		
Upper Portion 3*-6" ht. shall have 8 mm thick glass & 8 mm powder coated jaali on walls. Front of the cabin shall have horizontal gap of 2" width at the front so that customer & eashier can listen to each other. Lower 3*-6" Ht. Portion shall have pre—laminated board / Bison Board lovery color lixed in aluminum frame matching with the Ivory color lamination. Roof of the eashier cabin shall also have 8 mm thick powder coated jali. The rates also include fixing of stoppers, handles, hinges; door closer & Goderaj lock to the eashier door etc complete job in all respects. MANAGER CABIN PARITHON 5*-0" HT. P & F Manager Cabin Partition for aluminum 5*-0" Ht. of 4" x 1.75" x 2 mm ivory color powder coated pipe. Lower Portion 3*-6" Ht. shall have pre—laminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color lamination. Upper portion of the partition shall have 6 mm thick glass. The rates include u shaped neoprene gasket. 8. MAIN ENTERNCE DOOR & BACK DOOR (With Lock & Door Closer) P & F of aluminum door 8' ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3*-0" high portion of the door shall have pre—laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. FALSE CEILING (at 9*-0" high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting, If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges		Aluminum section shall be 4" x 1.75" x 2 mm ivory color powder				
powder coated jaali on walls. Front of the cabin shall have horizontal gap of 2" width at the front so that customer & cashier can listen to each other. Lower 3'-6" Ht. Portion shall have prelaminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color lamination. Roof of the cashier cabin shall also have 8 mm thick powder coated jali. The rates also include fixing of stoppers, handles, hinges; door closer & Goderaj lock to the cashier door etc complete job in all respects. MANAGER CABIN PARITHON 5'-0" HT. P & F Manager Cabin Partition of aluminum 5'-0" Ht. of 4" x 1.75" x 2 mm ivory color powder coated pipe. Lower Portion 3'-6" Ht. shall have pre -laminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color lamination. Upper portion of the partition shall have 6 mm thick glass. The rates include u shaped neoprene gasket. 8. MAIN ENTERANCE DOOR & BACK DOOR (With Lock & Door Closer) P & F of aluminum door 8" ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. FALSE CEILING (at 9'-0" high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 9 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting, If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including fi		coated. Partition shall have 8 mm thick glass on front & sides.				
horizontal gap of 2" width at the front so that customer & cashier can listen to each other. Lower 3'-6" Ht. Portion shall have pre—laminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color lamination. Roof of the eashier cabin shall also have 8 mm thick powder coated jali. The rates also include fixing of stoppers, handles, hinges; door closer & Goderaj lock to the eashier door etc complete job in all respects. MANAGER CABIN PARTITION 5'-0" HT. P & F Manager Cabin Partition of aluminum 5'-0" Ht. of 4" x 1.75" x 2 mm ivory color powder coated pipe. Lower Portion 3'-6" Ht. shall have pre—laminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color lamination. Upper portion of the partition shall have 6 mm thick glass. The rates include u shaped neoprene gasket. 8. MAIN ENTERANCE DOOR & BACK DOOR (With Lock & Door Closer) P & F of aluminum door 8' ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre—laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. FALSE CEILING (at 9'-0" high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in		Upper Portion 3'-6" ht. shall have 8 mm thick glass & 8 mm				
can listen to each other. Lower 3'-6' Ht. Portion shall have pre laminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color lamination. Roof of the eashier eabin shall also have 8 mm thick powder coated jali. The rates also include fixing of stoppers, handles, hinges; door closer & Goderaj lock to the eashier door etc complete job in all respects. MANAGER CABIN PARTITION 5'-0" HT. P & F Manager Cabin Partition of aluminum 5'-0" Ht. of 4" x 1.75" x 2 mm ivory color powder coated pipe. Lower Portion 3'-6" Ht. shall have pre -laminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color lamination. Upper portion of the partition shall have 6 mm thick glass. The rates include u shaped neoprene gasket. MAIN ENTERANCE DOOR & BACK DOOR (With Lock & Door Closer) P & F of aluminum door 8' ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. FALSE CEILING (at 9'-0" high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: Only the plan area will be measured for payment		powder coated jaali on walls. Front of the cabin shall have				
laminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color lamination. Roof of the eashier does include fixing of stoppers, handles, hinges; door closer & Goderaj lock to the eashier door ete complete job in all respects. MANAGER CABIN PARTITION 5°-0" HT. P & F Manager Cabin Partition of aluminum 5°-0" Ht. of 4" x 1.75" x 2 mm ivory color powder coated pipe. Lower Portion 3°-6" Ht. shall have pre-laminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color lamination. Upper portion of the partition shall have 6 mm thick glass. The rates include u shaped neoprene gasket. MAIN ENTERANCE DOOR & BACK DOOR (With Lock & Door Closer) P & F of aluminum door 8" ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. P FALSE CEILING (at 9"-0" high) P & F in position false eciling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. dueting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any		horizontal gap of 2" width at the front so that customer & cashier				
matching with the Ivory color lamination. Roof of the eashier cabin shall also have 8 mm thick powder coated jali. The rates also include fixing of stoppers, handles, hinges; door closer & Goderaj lock to the eashier door etc complete job in all respects. MANAGER CABIN PARTITION 5'-0" HT. P & F Manager Cabin Partition of aluminum 5'-0" Ht. of 4" x 1.75" x 2 mm ivory color powder coated pipe. Lower Portion 3'-6" Ht. shall have pre -laminated board / Bison Board Ivory color lixed in aluminum frame matching with the Ivory color lamination. Upper portion of the partition shall have 6 mm thick glass. The rates include u shaped neoprene gasket. 8. MAIN ENTERANCE DOOR & BACK DOOR (With Lock & Door Closer) P & F of aluminum door 8' ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. FALSE CEILING (at 9'-0" high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any		can listen to each other. Lower 3'-6" Ht. Portion shall have pre –				
shall also have 8 mm thick powder coated jali. The rates also include fixing of stoppers, handles, hinges; door closer & Goderaj lock to the cashier door etc complete job in all respects. MANAGER CABIN PARTITION 5'-0" HT. P & F Manager Cabin Partition of aluminum 5'-0" Ht. of 4" x 1.75" x 2 mm ivory color powder coated pipe. Lower Portion 3'-6" Ht. shall have pre -laminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color lamination. Upper portion of the partition shall have 6 mm thick glass. The rates include u shaped neoprene gasket. 8. MAIN ENTERANCE DOOR & BACK DOOR (With Lock & Door Closer) P & F of aluminum door 8' ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket, Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. FALSE CEILING (at 9'-0" high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any		laminated board / Bison Board Ivory color fixed in aluminum frame				
include fixing of stoppers, handles, hinges; door closer & Goderaj lock to the cashier door ete complete job in all respects. MANAGER CABIN PARTITION 5'-0" HT. P & F Manager Cabin Partition of aluminum 5'-0" Ht. of 4" x 1.75" x 2 mm ivory color powder coated pipe. Lower Portion 3'-6" Ht. shall have pre -laminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color lamination. Upper portion of the partition shall have 6 mm thick glass. The rates include u shaped neoprene gasket. 8. MAIN ENTERANCE DOOR & BACK DOOR (With Lock & Door Closer) P & F of aluminum door 8' ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. FALSE CELLING (at 9'-0" high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any		matching with the Ivory color lamination. Roof of the cashier cabin				
Sqft. Sqft.		shall also have 8 mm thick powder coated jali. The rates also				
MANAGER CABIN PARTITION 5'-0" HT. P & F Manager Cabin Partition of aluminum 5'-0" Ht. of 4" x 1.75" x 2 mm ivory color powder coated pipe. Lower Portion 3'-6" Ht. shall have pre -laminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color lamination. Upper portion of the partition shall have 6 mm thick glass. The rates include u shaped neoprene gasket. 8. MAIN ENTERANCE DOOR & BACK DOOR (With Lock & Door Closer) P & F of aluminum door 8' ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. FALSE CEILING (at 9'-0" high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any		include fixing of stoppers, handles, hinges; door closer & Goderaj				
P & F Manager Cabin Partition of aluminum 5'-0" Ht. of 4" x 1.75" x 2 mm ivory color powder coated pipe. Lower Portion 3'-6" Ht. shall have pre -laminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color lamination. Upper portion of the partition shall have 6 mm thick glass. The rates include u shaped neoprene gasket. 8. MAIN ENTERANCE DOOR & BACK DOOR (With Lock & Door Closer) P & F of aluminum door 8' ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. FALSE CEILING (at 9'-0" high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion pain etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any		lock to the cashier door etc complete job in all respects.			l l	
P & F Manager Cabin Partition of aluminum 5'-0" Ht. of 4" x 1.75" x 2 mm ivory color powder coated pipe. Lower Portion 3'-6" Ht. shall have pre -laminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color lamination. Upper portion of the partition shall have 6 mm thick glass. The rates include u shaped neoprene gasket. 8. MAIN ENTERANCE DOOR & BACK DOOR (With Lock & Door Closer) P & F of aluminum door 8' ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. FALSE CEILING (at 9'-0" high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any		MANAGER CABIN PARTITION 5'-0" HT.	90	Sqft.		
shall have pre -laminated board / Bison Board Ivory color fixed in aluminum frame matching with the Ivory color lamination. Upper portion of the partition shall have 6 mm thick glass. The rates include u shaped neoprene gasket. 8. MAIN ENTERANCE DOOR & BACK DOOR (With Lock & Door Closer) P & F of aluminum door 8' ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. FALSE CEILING (at 9'-0" high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any		P & F Manager Cabin Partition of aluminum 5'-0" Ht. of 4" x 1.75"				
aluminum frame matching with the Ivory color lamination. Upper portion of the partition shall have 6 mm thick glass. The rates include u shaped neoprene gasket. 8. MAIN ENTERANCE DOOR & BACK DOOR (With Lock & Door Closer) P & F of aluminum door 8' ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. FALSE CEILING (at 9'-0" high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any		x 2 mm ivory color powder coated pipe. Lower Portion 3'-6" Ht.				
portion of the partition shall have 6 mm thick glass. The rates include u shaped neoprene gasket. 8. MAIN ENTERANCE DOOR & BACK DOOR (With Lock & Door Closer) P & F of aluminum door 8' ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. FALSE CEILING (at 9'-0" high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any		shall have pre -laminated board / Bison Board Ivory color fixed in				
include u shaped neoprene gasket. MAIN ENTERANCE DOOR & BACK DOOR (With Lock & Door Closer) P & F of aluminum door 8' ht. high as per design. The aluminum section should be 4'x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. FALSE CEILING (at 9'-0" high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any		aluminum frame matching with the Ivory color lamination. Upper				
8. MAIN ENTERANCE DOOR & BACK DOOR (With Lock & Door Closer) P & F of aluminum door 8' ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. FALSE CEILING (at 9'-0" high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any		portion of the partition shall have 6 mm thick glass. The rates				
(With Lock & Door Closer) P & F of aluminum door 8' ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. FALSE CEILING (at 9'-0" high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any						
(With Lock & Door Closer) P & F of aluminum door 8' ht. high as per design. The aluminum section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. FALSE CEILING (at 9'-0" high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any	8.		110	Sqft.		
section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. FALSE CEILING (at 9'-0" high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any				· 1		
section should be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder coated. The lower 3'-0" high portion of the door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. FALSE CEILING (at 9'-0" high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any		P & F of aluminum door 8' ht. high as per design. The aluminum				
door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. FALSE CEILING (at 9'-0" high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any		section should be 4"x 1.75" x 2 mm for frame & panel shall be				
door shall have pre- laminated board / Bison Board fixed in aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. FALSE CEILING (at 9'-0" high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any		ivory colored powder coated. The lower 3'-0" high portion of the				
aluminum frame of ivory color. Upper part shall have 6 mm thick glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. FALSE CEILING (at 9'-0" high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any		door shall have pre- laminated board / Bison Board fixed in				
glass. These aluminum frames includes channels, beading & u shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. FALSE CEILING (at 9'-0" high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any		aluminum frame of ivory color. Upper part shall have 6 mm thick				
shaped neoprene gasket. Rates includes providing & fitting of all hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. FALSE CEILING (at 9'-0" high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any		glass. These aluminum frames includes channels, beading & u				
hardware items such as Godrej locks, stoppers, handles, door closer, hinges etc., i.e. Complete job in all respects. 9. FALSE CEILING (at 9'-0" high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any		shaped neoprene gasket. Rates includes providing & fitting of all				
hinges etc., i.e. Complete job in all respects. 9. FALSE CEILING (at 9'-0" high) P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any		hardware items such as Godrej locks, stoppers, handles, door closer,				
P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any		hinges etc., i.e. Complete job in all respects.				
P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16 mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any	9.	FALSE CEILING (at 9'-0" high)	850	Sqft.		
mm Dune Supreme RH 99 Prima file as specified by Armstrong Co. with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any		P & F in position false ceiling in Armstrong 600 X 600 mm x 15/16		1		
with suspenders wherever required making necessary cutouts for A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any		mm Dune Supreme RH 99 Prima file as specified by Armstrong Co.				
A.C. ducting. If any and necessary cutouts for diffusers and light fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any		with suspenders wherever required making necessary cutouts for				
fittings, taping and finished to proper line & level including making groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any		A.C. ducting. If any and necessary cutouts for diffusers and light				
groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any		fittings, taping and finished to proper line & level including making				
plywood with stainless steel hinges & locks with molding 1" x 1" for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any		groves and trap doors for A.C. Unit in 18 mm thick M.R. Grade				
for edges, if any including finishing with white plastic emulsion paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any		plywood with stainless steel hinges & locks with molding 1" x 1"				
paint etc. complete in all respects. (Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any		for edges, if any including finishing with white plastic emulsion				
(Note: - Only the plan area will be measured for payment. No extra payment will be made for cutouts, grooves, moldings, steps or any		paint etc. complete in all respects.				
payment will be made for cutouts, grooves, moldings, steps or any		(Note: - Only the plan area will be measured for payment. No extra				
type of design etc.)		payment will be made for cutouts, grooves, moldings, steps or any				
type of design etc.)		type of design etc.)				

T

Let' X 3'-6" X 1'-3") (1 CABINET) & F Cupboards made of 19, thick-laminated commercial board. pboards shell be divided into three parts horizontally. Vertically shall have partition after every 18". All the surfaces of the oboard from inside as well outside, shell be covered with 1mm ck laminate of Cedar white. The shutters shall have CAM locks, adles, auto closer hinges, magnate tic catchers etc. of approved tke. All the exposed edges of commercial board shall be incealed with 2.0 mm PVC edges binding; The internal surface all be finished with French spirit polish work incudes or fittings, ages locks and catchers etc. 10'-0" x 3'-6", Depth - 1'-6". DUCHER STAND Funcher stand of size 4'-0"x 3'-0" x 1'-0" made of 19 mm Antimite commercial board. All exterior surfaces shall have 1 mm ck laminate including partition boxes. It shall have 5 partitions a keeping vouchers. All edges shall have teak wood margin olding with duly polished in burgundy color (Bank Shade). DTICE BOARD Tice board of size 4'-0" x 2'-0" made of 19 mm anti termite mmercial board at back. Board shall be covered with 12 mm thick otexee board & matty fabric of burgundy color. Front & all side	1	No No		
boboard from inside as well outside, shell be covered with 1mm ck laminate of Cedar white. The shutters shall have CAM locks, adles, auto closer hinges, magnate tic catchers etc. of approved tike. All the exposed edges of commercial board shall be incealed with 2.0 mm PVC edges binding; The internal surface all be finished with French spirit polish work incudes or fittings, ages locks and catchers etc. 10'-0" x 3'-6", Depth - 1'-6". DUCHER STAND butcher stand of size 4'-0"x 3'-0" x 1'-0" made of 19 mm Antimite commercial board. All exterior surfaces shall have 1 mm ck laminate including partition boxes. It shall have 5 partitions keeping vouchers. All edges shall have teak wood margin olding with duly polished in burgundy color (Bank Shade). DTICE BOARD tice board of size 4'-0" x 2'-0" made of 19 mm anti termite mmercial board at back. Board shall be covered with 12 mm thick				
ndles, auto closer hinges, magnate tic catchers etc. of approved tike. All the exposed edges of commercial board shall be incealed with 2.0 mm PVC edges binding; The internal surface all be finished with French spirit polish work incudes or fittings, ages locks and catchers etc. 10'-0" x 3'-6", Depth - 1'-6". DUCHER STAND sucher stand of size 4'-0"x 3'-0" x 1'-0," made of 19 mm Antimite commercial board. All exterior surfaces shall have 1mm ek laminate including partition boxes. It shall have 5 partitions keeping vouchers. All edges shall have teak wood margin olding with duly polished in burgundy color (Bank Shade). DTICE BOARD stice board of size 4'-0" x 2'-0" made of 19 mm anti termite mmercial board at back. Board shall be covered with 12 mm thick				
ncealed with 2.0 mm PVC edges binding; The internal surface all be finished with French spirit polish work incudes or fittings, ages locks and catchers etc. 10'-0" x 3'-6", Depth - 1'-6". DUCHER STAND Further stand of size 4'-0"x 3'-0" x 1'-0" made of 19 mm Antimite commercial board. All exterior surfaces shall have 1mm ck laminate including partition boxes. It shall have 5 partitions keeping vouchers. All edges shall have teak wood margin olding with duly polished in burgundy color (Bank Shade). DTICE BOARD Stice board of size 4'-0" x 2'-0" made of 19 mm anti termite mmercial board at back. Board shall be covered with 12 mm thick				
all be finished with French spirit polish work incudes or fittings, ages locks and catchers etc. 10'-0" x 3'-6", Depth - 1'-6". DUCHER STAND Ducher stand of size 4'-0"x 3'-0" x 1'-0" made of 19 mm Antimite commercial board. All exterior surfaces shall have 1mm ck laminate including partition boxes. It shall have 5 partitions keeping vouchers. All edges shall have teak wood margin olding with duly polished in burgundy color (Bank Shade). DTICE BOARD Dtice board of size 4'-0" x 2'-0" made of 19 mm anti termite mmercial board at back. Board shall be covered with 12 mm thick				
DUCHER STAND Sucher stand of size 4'-0"x 3'-0" x 1'-0" made of 19 mm Antimite commercial board. All exterior surfaces shall have 1mm ck laminate including partition boxes. It shall have 5 partitions keeping vouchers. All edges shall have teak wood margin olding with duly polished in burgundy color (Bank Shade). DTICE BOARD Stice board of size 4'-0" x 2'-0" made of 19 mm anti termite mmercial board at back. Board shall be covered with 12 mm thick				
oucher stand of size 4'-0"x 3'-0" x 1'-0" made of 19 mm Antimite commercial board. All exterior surfaces shall have 1mm ck laminate including partition boxes. It shall have 5 partitions keeping vouchers. All edges shall have teak wood margin olding with duly polished in burgundy color (Bank Shade). OTICE BOARD stice board of size 4'-0" x 2'-0" made of 19 mm anti termite mmercial board at back. Board shall be covered with 12 mm thick				
mite commercial board. All exterior surfaces shall have 1mm ck laminate including partition boxes. It shall have 5 partitions keeping vouchers. All edges shall have teak wood margin olding with duly polished in burgundy color (Bank Shade). OTICE BOARD tice board of size 4'-0" x 2'-0" made of 19 mm anti termite mmercial board at back. Board shall be covered with 12 mm thick	1	No		
OTICE BOARD tice board of size 4'-0" x 2'-0" made of 19 mm anti termite mmercial board at back. Board shall be covered with 12 mm thick	1	No		
mmercial board at back. Board shall be covered with 12 mm thick				
otexee board & matty fabric of burgundy color. Front & all side				
all be covered with 1mm thick laminate. All edges shall be vered with teak wood margin/ molding and duly polished				
rgundy (Bank Shade).				
GGESTION BOX	1	No.		
ggestion box of size 1'-0" x 1'-0" x 9" made of 19mm thick				
		is .		
	1	No.		
day at the contract of the con				
	120	Saft		
,	120	Sqrt.		
Sec. (2014) 1991				
	ggestion box of size 1'-0" x 1'-0" x 9" made of 19mm thick mmercial board. All exposed surfaces shall be covered with 1mm ck laminate of white cedar color. Edges Shall be covered with 1k wood margin/ molding. It shall be polished in burgundy color ank color). A slit opening of 10 mm 22150mm is o be provided at a top of the box an open able shutter made of 19mm thick drop ard is to be provided. Proper arrangement for locks shall be made the contractor. DE TABLE (2'-0" x 2'-0") F keeping in position side table made out of 3/4" commercial ard, CP T/Wd rigid framing 1.5" X 1.5" size wood. The table top all be of 3/4" thick block board and in mica laminate 1.0 m thick of bank shade. All wood works shall be wax/spirit lished over a coat of Linseed oil finish. JP BOARDS ON STATIONARY ROOM, STRONG ROOM UPS ROOM & F Cupboards made of 19mm, commercial board. Cup boards all be divided by vertical after every 18" into equal parts. All posed surfaces shall have 1mm thick laminate inside and outside. ork includes complete accessories, hinges, Lock, handles, tehers etc. DTAL ST (18 %) RAND TOTAL	ggestion box of size 1'-0" x 1'-0" x 9" made of 19mm thick mmercial board. All exposed surfaces shall be covered with 1mm ck laminate of white cedar color. Edges Shall be covered with 1k wood margin/ molding. It shall be polished in burgundy color ank color). A slit opening of 10 mm 22150mm is o be provided at e top of the box an open able shutter made of 19mm thick drop ard is to be provided. Proper arrangement for locks shall be made the contractor. DE TABLE (2'-0" x 2'-0") F keeping in position side table made out of 3/4" commercial ard, CP T/Wd rigid framing 1.5" X 1.5" size wood. The table top all be of 3/4" thick block board and in mica laminate 1.0 m thick of bank shade. All wood works shall be wax/spirit lished over a coat of Linseed oil finish. JP BOARDS ON STATIONARY ROOM, STRONG ROOM WF Cupboards made of 19mm, commercial board. Cup boards all be divided by vertical after every 18" into equal parts. All posed surfaces shall have 1mm thick laminate inside and outside. ork includes complete accessories, hinges, Lock, handles, tehers etc. DTAL ST (18 %)	ggestion box of size 1'-0" x 1'-0" x 9" made of 19mm thick mmercial board. All exposed surfaces shall be covered with 1mm ck laminate of white cedar color. Edges Shall be covered with 1k wood margin/ molding. It shall be polished in burgundy color ank color). A slit opening of 10 mm 22150mm is o be provided at e top of the box an open able shutter made of 19mm thick drop and is to be provided. Proper arrangement for locks shall be made the contractor. DE TABLE (2'-0" x 2'-0") F keeping in position side table made out of 3/4" commercial and, CP T/Wd rigid framing 1.5" X 1.5" size wood. The table top all be of 3/4" thick block board and in mica laminate 1.0 m thick of bank shade. All wood works shall be wax/spirit lished over a coat of Linseed oil finish. JP BOARDS ON STATIONARY ROOM, STRONG ROOM UPS ROOM & F Cupboards made of 19mm, commercial board. Cup boards all be divided by vertical after every 18" into equal parts. All posed surfaces shall have 1mm thick laminate inside and outside. ork includes complete accessories, hinges, Lock, handles, tehers etc. OTAL ST (18 %)	ggestion box of size 1'-0" x 1'-0" x 9" made of 19mm thick mmercial board. All exposed surfaces shall be covered with 1mm ck laminate of white cedar color. Edges Shall be covered with 1k wood margin/ molding. It shall be polished in burgundy color ank color). A slit opening of 10 mm 22150mm is o be provided at the top of the box an open able shutter made of 19mm thick drop ard is to be provided. Proper arrangement for locks shall be made the contractor. DE TABLE (2'-0" x 2'-0") F keeping in position side table made out of 3/4" commercial ard, CP T/Wd rigid framing 1.5" X 1.5" size wood. The table top all be of 3/4" thick block board and in mica laminate 1.0 In thick of bank shade. All wood works shall be wax/spirit lished over a coat of Linseed oil finish. JP BOARDS ON STATIONARY ROOM, STRONG ROOM & F Cupboards made of 19mm, commercial board. Cup boards all be divided by vertical after every 18" into equal parts. All posed surfaces shall have 1mm thick laminate inside and outside. ork includes complete accessories, hinges, Lock, handles, tehers etc. DTAL ST (18 %)

Total in Words:

