				Annex	kure-10-A	
	FINANCIAL BID FOR FURNISHING WORK					
PUNJAB GRAMIN BANK, BRANCH - BO: THULIWAL, DISTT. BARNALA						
S. No.	Description of items	Qty	Unit	Rate	Amount	
	•			(In Rs.)	(In Rs.)	
1.	FALSE CEILING IN MAIN HALL DOOR & STRONG ROOM (AT 9'-0" HIGH)	750	Sq. ft.			
	This specification outlines the installation of a false ceiling using Armstrong Dune RH 99 Prima tiles (600x600mm, 15/16mm thick) with suspenders. The scope of work includes: 1. Making cutouts for AC ducting, diffusers, and light fittings. 2. Creating grooves and trap doors for AC units using 18mm M.R. Grade plywood. 3. Finishing with white plastic emulsion paint. Payment will be based on the plan area, with no extra payment for cutouts, grooves, or design features.					
2.	GYPSUM BOARD	360	Sq. ft.			
	This specification outlines the installation of a false ceiling using India Gypsum Ltd.'s GMFSC-4.1 material. The scope of work includes: Key Details 1. False ceiling height: 9'-0" (as per drawing) 2. G.I. section placement: 4'-0" c/c in one direction and 1'-6" c/c in the other direction 3. Finishing: Properly finished after cutting/making holes for light fixtures 4. Painting: Ceiling: Three coats of oil-bound enamel paint Vertical surfaces: Painted with Red Ruby color Completion The work shall be completed in all respects, ensuring a smooth and finished surface.		>			
3.	CLERICAL / OFFICER TABLE - No's - 4 (4'-6" x 2'-6" X 2'-6" Ht.)	18'-0"	Rft.			
	 Specification The CLERICAL / OFFICER's table shall be of size 4'-6" (L) x 2'-6" (W) x 2'-6" (H). One side of the table shall include one drawer fitted with Hettich ball-bearing slides, and a cabinet or storage space below for filing purposes. The table shall be constructed using 19mm thick commercial board. All exposed surfaces shall be laminated with 1mm thick high-gloss laminate. Table edges shall be finished with C.P.T.W. lipping, duly spirit-polished. All internal, non-visible surfaces shall be properly polished. The scope of work also includes: A teak wood (T.W.) shelf for placing the CPU A 3' x 1.5' teak wood footrest, duly polished Ebco Keyboard Tray (Code: KBT 45) Godrej accessories including locks, hinges, handles, and stoppers Provision for cable management (holes for computer wiring, etc.) 					

4.	CASHIER TABLE	5'-6"	Rft.	
	Cashier Counter Specification Providing and fixing a Cashier Counter of size 5'-6" (L) x 2'-6" (W) x 3'-9" (H), made from 19mm thick commercial board of Duro / Century / Kitply make. The counter shall be finished with 1mm thick Cedar White color laminate on all vertical, exposed, and visible surfaces. The counter shall include the following: • Ebco keyboard tray (Code: KBT 45) • Drawers fitted with Hettich ball-bearing slides, including partitions for currency and storage boxes • Marking and provision for electrical conduit points, switch boxes, and 2" diameter round plastic openings for cable management • U.P.S. shelf at the bottom • All necessary fittings and accessories including Godrej/Latch locks, handles, hinges, etc. • The lower 4" portion on the front and sides shall be finished with burgundy color laminate (Bank shade) • All exposed edges shall be finished with teak wood molding, duly polished The work shall be completed in all respects to ensure a fully functional and finished cashier counter.		Q.	
5.	MANAGER TABLE 6'-0" X 2'-6" WITH SIDE CREDENZA 3'-6" X 1'-6"X 2'-6"	1	Nos.	
6	Manager Table with Side Credenza – Specification Manager Table The Manager's table shall be of size 6'-0" (L) x 2'-6" (W) x 2'-6" (H). One side of the table shall include one drawer fitted with Hettich ballbearing slides, and a cabinet or storage unit below for filing purposes. The table shall be constructed from 19mm thick commercial board. All exposed surfaces shall be finished with 1mm thick high-gloss laminate. The edges of the table shall be finished with C.P.T.W. lipping, duly spirit-polished. All internal and non-visible portions shall be properly polished. The work shall include: A teakwood (T.W.) shelf for placing the CPU A 3' x 1.5' teakwood footrest, duly polished Provision for cable management, including holes for computer wiring Ebco Keyboard Tray (Code: KBT 45) All necessary accessories including Godrej locks, hinges, handles, and stoppers Side Credenza The side credenza shall include two filing drawers, each 18" wide and placed vertically. It shall be made of commercial board with 12mm laminated shelves. Both external and internal visible surfaces shall be laminated with 1mm thick high-gloss laminate on both sides. The entire setup shall be completed in all respects, ensuring a clean, polished, and functional finish.	1	Nos	
6.	MANAGER TABLE - TOP GLASS 6'-0" X 2'-6" X 8 MM WITH GRINDING OF EDGES & CORNERS.	1	Nos.	
7.	OFFICER TABLE & CLERICAL TABLE – TOP GLASS 4'-6" X 2'-6" X 8 MM WITH GRINDING OF EDGES & CORNERS.	4	Nos.	

8.	ALUMINIUM PARTITION				
	CASHIER CABIN 7' HT.	110	Sq. ft.		
	Cashier Cabin Partition Specification		•		
	The aluminum section shall be 4" x 1.75" x 2mm, powder-coated in ivory				
	color. The partition shall have 8mm thick glass on the front and sides.				
	The upper portion, with a height of 3'-6", shall consist of 8mm thick				
	glass and 8mm thick powder-coated perforated jaali on the walls.				
	The front of the cabin shall include a horizontal gap of 2" width to allow				
	clear communication between the customer and the cashier.				
	The lower 3'-6" portion shall be constructed using pre-laminated board				
	or Bison Board in ivory color, fixed within the aluminum frame to match				
	the laminated finish. The roof of the cashier cabin shall also include				
	8mm thick powder-coated jaali. The quoted rates shall include the				
	supply and installation of all necessary hardware such as stoppers,				
	handles, hinges, door closer, and a Godrej or ISI-marked auto-lock for				
	the cashier door — all to be completed in every respect.				
	MANAGER CABIN PARTITION 5'-0" HT.	100	Sq. ft.		
	Providing and Fixing Manager Cabin Partition				
	Providing and fixing a manager cabin partition with a height of 5'-0",				
	made using 4" x 1.75" x 2mm thick aluminum sections, powder-coated				
	in ivory color. The lower portion , up to 3'-6" height, shall consist of				
	12mm thick Bison Board, laminated on both sides in ivory color, fixed	*			
	within an aluminum frame matching the lamination. The upper portion				
	of the partition shall be fitted with 6mm thick clear glass. The quoted				
	rates shall include all necessary materials, fittings, and a U-shaped				
	neoprene gasket for secure and vibration-free glass installation.				
9.	STORAGE CABINET, STRONG ROOM & STATIONARY ROOM AT 4'	210	Sq. ft.		
	HT & KITCHEN UNDER SELF & AT 4'-0" HT, 2' HIGH. INCLUD				
	STORAGE FOR OFFEICER IN THE BANK HALL.				
	1. Storage shelves to be provided at 7'-0" height above existing				
	shelves in the Stationery and Strong Room.				
	2. In the Kitchen, shelves to be installed under the countertop and				
	at a height of 5'-0". Each shelf shall be 1'-6" high and 1'-6" in				
	length.				
	3. Storage units to be provided at the back of the Officer's cabin				
	(as per the layout/map) and in the hall area. These shall be				
	made using 19mm thick commercial board, laminated on both				
	sides with 1mm thick laminate.				
	Shelves in level areas shall also be laminated with 1mm thick laminate.				
	The scope of work includes all necessary accessories such as hinges,				
	handles, stoppers, and locks, ensuring a complete and functional installation.				
10		80	Df+		
10.	PARTITION BETWEEN TABLES & FRONT GLASS 10 mm Pigen Poord partition in between and side of the table 2' 0" v 4'	δU	Rft		
	19 mm Bison Board partition in between and side of the table 3'-0" x 4'-0". Upper portion of partition shall have 8 mm glass supported by				
	wooden partition. Partition shall have both side CEDAR WHITE colour				
	laminate. Edges shall have teak wood lipping duly polished. Front of the				
	table shall have 12 mm thick toughn glass with grinded edge (4'-6" x 5')				
	with 6" gap from table.				
11.	VOUCHER STAND	1	No		
11.	Providing and fixing a voucher stand of size 4'-0" (L) x 3'-0" (H) x 1'-0"	1	110		
	(D), made from 19mm thick anti-termite commercial board. All exterior				
	surfaces, including the partition boxes, shall be finished with 1mm thick				
	laminate. The stand shall have five partitions for organizing and storing				
	vouchers. All exposed edges shall be finished with teak wood margin				
	molding, duly polished in burgundy color (Bank shade).				
12.	NOTICE BOARD	1	No		
	Providing and fixing a notice board of size 4'-0" x 2'-0", made of 19mm				
	thick anti-termite commercial board at the back. The board shall be				
	covered with 12mm thick Celotex board and matting fabric in burgundy				
	color. The front and all sides of the notice board shall be covered with				
	1mm thick laminate. All edges shall be finished with teak wood				
	margin/molding, duly polished in burgundy (Bank Shade).				
	, , , persone meangains, (built online)	i		1	1

13.	SUGGESTION BOX	1	No.	
10.	Providing and fixing a suggestion box of size 1'-0" x 1'-0" x 9", made		110.	
	from 19mm thick commercial board. All exposed surfaces shall be			
	covered with 1mm thick laminate in white cedar color. The edges shall			
	be finished with teak wood margin/molding and polished in burgundy			
	color (Bank shade). A slit opening of 10mm x 150mm shall be provided			
	at the top of the box. An operable shutter, made of 19mm thick drop			
	board, shall be provided. Proper arrangements for locks shall be made			
	by the contractor.			
14.	STEEL SETTEE	1	No.	
	Providing of three Seater silver color steel settee.		1101	
15.	MAIN ENTERANCE DOOR	70	Sq. ft.	
10.	12 mm Thick Toughen Glass Door. It shall have two doors 3'-0" each		oq. 10	
	having size 3'-0" x 7'-0". Remaining portion shall have 12 mm fixed			
	glass. Rates includes providing & fitting of all hardware items such as			
	Godrej locks, stoppers, handles, door closer, hinges & Patch fitting etc.,			
	i.e. Complete job in all respects.			
16.	ALUMINIUM BACK DOOR 5'-0" X 8'-0"	45	Sq. ft.	
	(WITH LOCK & DOOR CLOSER)			
	Aluminum Door shall have 2 panel of 2'-6" x 7'-0"each. P & F of			
	aluminum door 8' Ht. high as per design. The aluminum section should			
	be 4"x 1.75" x 2 mm for frame & panel shall be ivory colored powder			
	coated. The lower 3'-0" high portion of the door shall have pre-			
	laminated board / Bison Board fixed in aluminum frame of ivory color.			
	Upper part shall have 6 mm thick glass. These aluminum frames			
	includes channels, beading & u shaped neoprene gasket. Rates includes			
	providing & fitting of all hardware items such as Godrej locks, stoppers,			
	handles, door closer, hinges etc., i.e. Complete job in all respects.			
	TOTAL			
	GST (18 %)			
	GRAND TOTAL			

TOTAL IN WORDS: